

RULES	
SW	Swivel
BS	Brake Side
BF	Brake Front
BR	Brake Rear
FX	Fixed
SLR	Swivel Lock on to Rigid
AJ	Adjustment
SWT	Swivel with Threaded Stem
BST	Brake Side with Threaded Stem
BFT	Brake Front with Threaded Stem
BRT	Brake Rear with Threaded Stem
SWM	Swivel Modular
BSM	Brake Side Modular
BFM	Brake Front Modular
BRM	Brake Rear Modular
SWR	Swivel with Round Stem
BSR	Brake Side with Round Stem
BFR	Brake Front with Round Stem
BRR	Brake Rear with Round Stem

HA	H Aluminum ; H- Rubber
GA	G Aluminum ; G- Grey Rubber
HS	H Steel ; H- Rubber
HG	HG- Rubber with nylon core
H	H- Rubber
PUA	PU Aluminum
PUS	PU Steel
NL	NL- Nylon
NLP	NLP- Nylon with Ball Bearing (P)
NLR	NLR- Nylon with Roller Bearing (R)
NLS	NLS- Nylon with Sleeve Bearing (S)
PH	PH- Phenolic
PHP	PH- Phenolic with Ball Bearing (P)
PHR	PH- Phenolic with Roller Bearing (R)
B	B (Black Polypropylene)
W	W (White Polypropylene)
TPR	TPR
TPU	TPU
HA-EC	H + Electrical Conductor
TPR-EC	TPR + Electrical Conductor
HA-HR	H High temp. Resistance
-PC	Protective Cover +ESD
#304	#304 Stainless Steel
DW	Dual Wheel- DW